


CAUTION: MAXIMUM OUTPUT SHAFT SPEED NOT TO EXCEED 2,500 RPM.


ALLISON TRANSMISSION		
	4000*** SERIES MUNCIE PTO SHAFT EXTENSIONS <small>*** (EVS, RDS, SPS, OFS) (MHS, BUS, TRV OPTIONAL) HD-4060P, HD-4560P, HD-4070P</small> Footnotes (1, 2, 3, & 4)	ALLISON 10-BOLT OPENING PTO DRIVE GEAR DATA: <small>97T 10.16P L.H.</small> LOCATION: Front PLMF: 1.775 PLV: 2648 FPM RPM: 1,000

ALLISON 4000*** WITHOUT RETARDER OR COOLER		
PTO SERIES	LEFT SIDE	TOP SIDE
A20	XSMC-A40XX-X3**XX A20-A10**-HX3CBPW	XSMC-A40XX-X5**XX A20-A10**-HX5CBPW
A30	XSMC-A40XX-X3**XX A30-A10**-MX3CBPW	XSMC-A40XX-X5**XX A30-A10**-MX5CBPW
A40	XSHD-A40XX-X3**XX A40-A10**-HX3CBPW	XSHD-A40XX-X5**XX A40-A10**-HX5CBPW
A50	XSHD-A40XX-X3**XX A50-A10**-MX3CBPW	XSHD-A40XX-X5**XX A50-A10**-MX5CBPW
ALLISON 4700*** WITHOUT RETARDER OR COOLER		
PTO SERIES	LEFT SIDE	TOP SIDE
A20	XSMC-A47XX-X3**XX A20-A10**-HX3CBPW	XSMC-A47XX-X5**XX A20-A10**-HX5CBPW
A30	XSMC-A47XX-X3**XX A30-A10**-MX3CBPW	XSMC-A47XX-X5**XX A30-A10**-MX5CBPW
A40	XSHD-A47XX-X3**XX A40-A10**-HX3CBPW	XSHD-A47XX-X5**XX A40-A10**-HX5CBPW
A50	XSHD-A47XX-X3**XX A50-A10**-MX3CBPW	XSHD-A47XX-X5**XX A50-A10**-MX5CBPW
ALLISON 4000*** WITH RETARDER		
PTO SERIES	LEFT SIDE	TOP SIDE
A20	XSMC-A40XX-X4**RX A20-A10**-HX5CBPW	NOT AVAILABLE
A30	XSMC-A40XX-X4**RX A30-A10**-MX5CBPW	NOT AVAILABLE
A40	XSHD-A40XX-X4**RX A40-A10**-HX5CBPW	NOT AVAILABLE
A50	XSHD-A40XX-X4**RX A50-A10**-MX5CBPW	NOT AVAILABLE

IMPORTANT: FOOTNOTES MAY AFFECT PTO SELECTION

- 1 PTOs and shaft extensions for integral cooler applications must be mounted shaft high in order to clear cooler..
- 2 PTO and shaft extension sold separately. Table shows shaft extension part number on top, with corresponding PTO listed below where applicable. Some combinations are not available, and are listed as such.
- 3 Shaft extensions for Allison 4700 Series transmission are only available for standard transmission without retarder. Top opening on 4700 with integral cooler can use standard top mount shaft extension option. No option for 4700 left side opening with integral cooler. SAE outputs only. DIN output not available..
- 4 See page ALLI-06 for PTO application details.

CAUTION: MAXIMUM OUTPUT SHAFT SPEED NOT TO EXCEED 2,500 RPM.

ALLISON TRANSMISSION		
	4000*** SERIES MUNCIE PTO SHAFT EXTENSIONS *** (EVS, RDS, SPS, OFS) (MHS, BUS, TRV OPTIONAL) HD-4060P, HD-4560P, HD-4070P Footnotes (1, 2, 3, & 4)	ALLISON 10-BOLT OPENING PTO DRIVE GEAR DATA: 97T 10.16P L.H. LOCATION: Front PLMF: 1.775 PLV: 2648 FPM RPM: 1,000
	ALLISON 4000*** WITH INTEGRAL COOLER	
PTO SERIES	LEFT SIDE	TOP SIDE
A20	XSMC-A40XX-X4**CX A20-A10**-HX5CBPW	XSMC-A40XX-X5**XX A20-A10**-HX5CBPW
A30	XSMC-A40XX-X4**CX A30-A10**-MX5CBPW	XSMC-A40XX-X5**XX A30-A10**-MX5CBPW
A40	XSHD-A40XX-X4**CX A40-A10**-HX5CBPW	XSHD-A40XX-X5**XX A40-A10**-HX5CBPW
A50	XSHD-A40XX-X4**CX A50-A10**-MX5CBPW	XSHD-A40XX-X5**XX A50-A10**-MX5CBPW

IMPORTANT: FOOTNOTES MAY AFFECT PTO SELECTION

- 1 PTOs and shaft extensions for integral cooler applications must be mounted shaft high in order to clear cooler..
- 2 PTO and shaft extension sold separately. Table shows shaft extension part number on top, with corresponding PTO listed below where applicable. Some combinations are not available, and are listed as such.
- 3 Shaft extensions for Allison 4700 Series transmission are only available for standard transmission without retarder. Top opening on 4700 with integral cooler can use standard top mount shaft extension option. No option for 4700 left side opening with integral cooler. SAE outputs only. DIN output not available..
- 4 See page ALLI-06 for PTO application details.